Head Office and Showroom:

Davy Avenue, Knowlhill Milton Keynes, MK5 8HJ United Kingdom Tel: (0)1908 608888

Fax: (0)1908 692399 www.morgana.co.uk sales@morgana.co.uk



Countron Touch

The perfect solution for high speed counting.

Key product features:

- Counts up to 2200 sheets per minute
- Counts stocks up to from 22-255gsm
- Tab insertion for separating printed batches
- Pile height (up to 300mm)
- Easy to use touch screen operation


Accurate, high-speed counting is assured for various qualities and thicknesses of paper such as offset paper, coated paper, digital printed paper and thin invoices etc.

With a large touch screen, setting adjustments are quick and easy to make, along with clear diagnosis of any errors during operation.

Functions available in addition to normal counting mode include the random tab insertion function for separating various numbers of sheets with tab tapes. Other functions include a sheet-number check function which checks when the actual counted number of sheets matches a pre-set number of sheets, and an appointed number counting systems which helps set aside a desired number of sheets from a stack of paper.



Inserting paper tabs in between batches can save hours of laborious manual job splitting before and after the print finishing process.



Countron Touch

The perfect solution for high speed counting.



Technical specifications

Basic function	Count, tab tape insertion (every 2 to 1,000 sheets)
Maximum paper size	546(W) x 788(L) mm
Minimum paper size	210(W) x 210(L) mm
Minimum finished work size	100(W) x 150(L) mm
Paper weight	22-255gsm
Operation	Touch screen
Max pile height	300mm
Speed (* Target speed)	0 to 2200* sheets per minute
Dimensions (approx)	W900 x D1086x H1350mm
NET Weight (approx)	150kg
Power supply	110,115, 220, 230, 240 VAC, 50/60Hz

^{(*} Target speed)

As part of our continued product improvement plan, specifications and information published here are subject to change without notice. All specifications are dependent on application, type of stock, temperature, RH and print engine used. Specifications quoted were measured on uncoated and unprinted stock. E & OE.

^{*}Disclaimer