ONYX SERIES





The HD8000 offers a 14 inch (356 mm) legal size capacity and closes books from 3/16 inch to 1-1/4 inch thick (5 mm to 32 mm). The settings for wire sizes are fast and accurate, providing a significant savings on wire costs: wire that is spoiled during the set-up and adjustment of competitive closers. An available optional wire hanger attaches to the HD8000 and holds the wire in position to hang punched sheets onto the double loop wire.



More than **98%** recyclable



PRODUCT FEATURES

- Dual adjusting closing feature left and right knobs to ensure even wire closing.
- Reversible binding handle for right or left-handed operation.
- Exclusive reversible top closing bar choose abrasive or smooth closing surface depending on operator preference or wire size.
- Optional raised front feet elevates front of machine, improving viewing and wire positioning.

- Wire compatibility from 3/16 inch (5 mm) to 1 ¼ inch (32 mm) sizes.
- Wide 14 inch (356 mm) throat, plus an open-ended design for even larger projects.
- Stand-alone operation, or mounts on most Rhin-O-Tuff Punches (with optional Mounting Kit).
- > Durable all-metal construction.
- > 3 Year Warranty.

MACHINE SPECIFICATIONS

| Electrical Requirements | | | Weight | | Assembled Dimensions | | |
|--------------------------------|------|----|---------|----------|----------------------|--------|--------|
| Volts AC | AMPS | Hz | Machine | Shipping | Height | Width | Depth |
| NA | NA | NA | 19 lbs. | 23 lbs. | 14"* | 17" | 13" |
| NA | NA | NA | 8.6 Kg | 10.5 Kg | 355 mm | 432 mm | 330 mm |

*with handle in upright position.

Telefon: +46 8 602 50 00 | Fax: +46 8 722 99 70 Besöksadress:Telefonvägen 30 SE-126 26 HÄGERSTEN | SWEDEN | info@pdfab.se

